

## Technical Information

No. DO 5109

Edition: 08/08 - subject to change

Supersedes 08/02

Status: valid

Tungsten Halogen Lamp  
for Airfield Lighting


# 64317 IRC-C

### ■ Product description

The OSRAM 64317 IRC-C is a tungsten halogen lamp with 10% more light output as a standard 45W lamp and with triple lifetime. It is comparable to the 64319 IRC-A but with 16.0 mm instead of 20.0 mm LCL and is used for the following applications:

Taxiway centre line, stopbar, runway edge, taxiway edge, runway end, threshold and approach lighting.

### ■ Technical data

Order reference		64317 IRC-C 45-30
LIF		J1/76
Maximum operation current	A	6.6
Base		PK30d
Connector		C male <sup>1</sup>
Cable length	mm	min. 125
Rated lamp wattage	W	45
Maximum initial wattage	W	47
Average life	h	3,000
Color temperature	K	3,000
Rated luminous flux	lm	900
Minimum initial luminous flux	lm	810
Luminous flux after 2,250 h	lm	min. 90% of initial value
Bulb diameter (d)	mm	max. 15
Length (l <sub>1</sub> )	mm	max. 28
Length (l <sub>2</sub> )	mm	max. 20
LCL (a)	mm	16.0
Filament type		C-8
Filament dimensions (w x h)	mm	2.1 x 2.9
Deviation of filament centre	mm	max. 1.0 (refers to base axis)

### ■ Lamp operation

Burning position		s 90
Maximum pinch temperature	°C	350
Chromaticity		within white boundaries as defined in Annex 14 to the Convention of International Civil Aviation

<sup>1</sup> Male connector C complies with DIN 46248

